

ICS CORE DRILL STAND

PRODUCT DATASHEET
DPT-L200-2-ICS

DPT-L200-2-ICS
FOR DPT MICRO-PERCUSSION



FITS:
DPT2200-ME-36-120V
DPT2200-SE-36-120V
DPT3000-ME-37-120V

Specifications

Base	Compact and Light Aluminum Base
Column	Extruded Aluminum 2" x 2" / 5 cm x 5 cm
Carriage	Self Lubricating Sliding Pads
Feeding Handle	DPT Anti-Vibration Technology Vibrations reduced by 50%
Max Carriage Run	22.75" / 57.7 cm
Rear Bars	Steel - 2 Bars
Tilting Angle	From 0° - 45°
Fixing System	With Anchor
Core Drill Mounting	60 mm Collar for Hand-Held Core Drills Rapid Quick-Lock Connection
Max Drilling Diameter	10" / 25 cm
Weight	29.3 lbs / 13.3 kg
Dimensions L x W x H	16" x 12.5" x 32" / 40 cm x 33 cm x 86 cm
Includes 19mm Spanner & 6 mm Allen Key	

Core Drill, Stand and
Core bit sold separately



Diamond Tools and Equipment

ICSDIAMONDTOOLS.COM | 800.321.1240

Effective January 1, 2025 | Copyright 2025 ICS, Oregon Tool Inc. Pricing, product offerings and specifications are subject to change without notice. FORCE3, FORCE4, PowerGrit, SpeedHook, SealPRO, and WallWalker are registered trademarks of ICS. The best way to cut concrete, DCT, Speed King, TSS, Trident and ProFORCE are trademarks of ICS. Rev: 012025.